


# ALFRA ROTABEST® – RB 50 SP



## RB 50 SP

<b>Core drill dimensions</b>	Ø 12.0 - 50.0 mm
<b>Cutting depth</b>	50.0 mm
<b>Twist drill</b>	Ø 1.0 - 20.0 mm
<b>Counterboring</b>	Ø 10.0 - 40.0 mm
<b>Arbors</b>	Quick-release chuck MT2
<b>Stroke</b>	100 mm
<b>Height adjustment</b>	47 mm
<b>Gearbox - on-load speed</b>	1. Step 250 rpm 2. Step 450 rpm
<b>Power consumption</b>	1,200 W
<b>Voltage</b>	230 V 50/60 Hz 110 V 50/60 Hz
<b>Tool Force (10 mm) / Magnetic adhesion force</b>	2,800 N/8,000 N
<b>Tool force (6 mm S235)</b>	2,000 N
<b>Magnetic base</b>	72 x 190 mm
<b>Weight</b>	11.5 kg

<b>Motor</b>	
Smooth start	✓
Hybrid relay	✓
Overload protection	✓
Motor emergency stop	✓
<b>Gearboxes</b>	
Oil bath gearbox	✓
<b>Slide</b>	
Infinitely adjustable	✓
Self-adjusting guide	✓
<b>Operation</b>	
Soft-touch grips	✓
Membrane keyboard	✓
Holder for Allen key	✓
Cable length 5 m	✓
<b>Magnet</b>	
Sensor/LED	✓
TiN-coating	✓
Performance and weight optimisation	✓
<b>Made in Germany</b>	✓

<b>Scope of delivery</b>	
<ul style="list-style-type: none"> <li>• Metal core drilling machine RB 50 SP</li> <li>• Tool holder MT 2 with quick-release chuck, including internal cooling</li> <li>• Carrying case</li> <li>• Seat belt</li> <li>• Coolant device</li> <li>• Operating Instructions</li> <li>• <b>incl. 1 core drill free</b></li> </ul>	

**Prod.-No.**

ALFRA Rotabest® RB 50 SP 230 Volt

18851

ALFRA Rotabest® RB 50 SP 110 Volt

18851.110