

ROTABEST® – RB 50 X VACUBEST

Product features Rotabest® RB 50 X Vacubest:

- Automatic shut-off of motor in case of vacuum loss
- Adjustable laser cross
- Machine is mounted on the vacuum plate rotatable by 270°
- Vacuum pump can be controlled by the core drilling machine

Use on non-magnetic surfaces such as aluminium, copper, brass, stainless steel, plastics, wood and textured surface (e.g. corrugated and chequer plate)

Technical specifications:

Core drilling in metal: Ø 12.0 - 50.0 mm

Drilling in wood: Ø 12.0 - 100.0 mm

Drilling depth: 50 mm

Power consumption: 1200 W

2 speed gearbox: 250/450 rpm

Arbor: available as 19 mm Weldon or MT2

Coolant feed: automatically integrated from the top through the spindle

Voltage: 230 volt or 110 volt
(50-60 Hz)

Vacuum adhesion force: 9000 N

Tool force
(at - 0.9 bar): 2300 N

Printing: - 0.9 bar / - 90kPa

Description

ALFRA – Rotabest® RB 50 X Vacubest with MT 2 mounting

Prod.-No.

18740

ALFRA – Rotabest® RB 50 X Vacubest with Weldon arbor

18740.WD

ALFRA – Rotabest® RB 50 X Vacubest with MT 2 arbor, 110v

18740.110.UL

