ECO.40/2









40_{mm}















1050 W 1500

150_{mm}

High speed gearing Specially designed for twist drilling

With a touch of overcapacity, working is even more fun. The ECO.40 magnetic drilling machine has a powerfull motor and can be mechanically adjusted to two rotational speeds.

Higher spindle speed makes this machine particularly suitable for twist drilling.







- 2-speed gearbox
- Compact design
- Detachable spindle
- Practical long stroke
- Clear and easy controls















≤ Ø 40 mm page: 70	≤ Ø 13 mm page: 96	≤ Ø 45 mm page: 95	accessories page: 61
1/9//	27		
	W		

Technical data

Annular cutters	Ø 12 - 40 mm	
Twist drills	Ø 1 - 13 mm	
Countersinking	Ø up to 45 mm	
Length	320 mm	
Width	210 mm	
Height	395 - 540 mm	
Stroke	150 mm	
Weight	12 kg	
Magnet (I x w x h)	160 x 80 x 42 mm	
Magnetic force	1500 kg	
Motor power	1050 W	
Total power	1100 W	
Speed (no load)	(I) 720 min ⁻¹	
Speed (no load)	(II) 1300 min ⁻¹	
Speed (load 1050 W)	(I) 315 min ⁻¹	
Speed (load 1050 W)	(II) 560 min ⁻¹	
Spindle (Weldon)	3/4" (19,05 mm)	
Voltage	110-120 / 220-240 V / 50-60 Hz	

- 1 Ergonomic feed handle
- 2 High precision height adjustment: Low maintenance, minimal wear correction
- 3 Strong dual coil CNC machined magnet
- 4 Clear and easy controls
- 5 Detachable spindle
- 6 Integrated tool cooling
- 7 2-speed gearbox