F16







See icon guide on cover flap














1200



Flexible universal drill stand with plug connection for hand drills with twistdrill capacity up to 16 mm. Thanks to the plug connection the operator is offered central switch operation. The F16 enables you to drill, tap, ream and countersink perfectly straight with high stabillity. The high power magnet force of 1200kg offers a secure grip hold during your operation.



















Features

- 43mm Euro collar connection (optional 33mm and 38mm filler rings included)
- Perfect solution for high precision small diameter drilling tasks
- User friendly controls
- Every F16 is delivered fully equipped in a sturdy and organized suitcase

Technical data

Countersink up to Ø 35 mm Length 310 mm	Twist drills	up to Ø 16 mm
Length 310 mm	Countersink	up to Ø 35 mm
	Length	310 mm
Width 170 mm	Width	170 mm
Height 325 - 495 mm	Height	325 - 495 mm
Stroke 170 mm	Stroke	170 mm
Weight 13,6 kg	Weight	13,6 kg
Magnet (I x w x h) 160 x 80 x 36 mm	Magnet (I x w x h)	160 x 80 x 36 mm
Magnetic force 1200 kg	Magnetic force	1200 kg
Voltage 110V/220V - 50/60 Hz	Voltage	110V/220V - 50/60 Hz

Example of application

≤ Ø 35 ≤ Ø 16

- 1 Safe and easy rear mounted socket
- 2 Ergonomic feed handle
- 3 High accuracy capstan hub
- 4 High precision height adjustment: Low maintenance, minimal wear correction
- 5 Strong dual coil CNC machined magnet
- 6 Clear and easy controls

Technical specifications based on structural and magnet holding capacity.