

Finishing machine for metal surface with useful working width up to 300 mm and thickness up to 170 mm. The smallest of deburring Gecam that can mounts up to 3 working groups, with configuration variable according to the working needs.

Rigid feeding table equipped with a conveyor belt super-grip profile for piece high stability while working, manually height adjustment.

- *Digital display for thickness control*
- *Rubber pressure drums placed in front and behind each working units, adjustable height*
- *2 speeds 5/10 m/min*
- *Motor 0,75kW*
- *Standard voltage 400 Volt*

Control panel easy to use with general switch connected to the emergency systems

- *Switch to manual control of each working unit*
- *Safety pressure switch for compressed air presence*

WORKING GROUP “R” – ABRASIVE BELT GROUP

Abrasive belt with rotation in the workpiece feeding direction , equipped with pneumatic grinding belt oscillating

Rubber, spirally grooved drum 55° shore and diameter 125 mm.

Available under request 30° and 45° shore.

Independent motor 4kW power

Belt speed 15m/sec

WORKING GROUP “T” – TOP BRUSHES

Top brushes group rotating and oscillating with diameter 115 mm. Standard configuration mounts mixed brushes scotch brite and abrasive belt

Independent motor 3kW power

Cutting speed 12m/sec

WORKING GROUP “B” – CYLINDRICAL BRUSH

Longitudinal cylindrical brush with in-feed rotation, diameter 150 mm

TECHNICAL DATA

<i>Working width</i>	<i>300 mm</i>
<i>Working thickness</i>	<i>0,5 -160 mm</i>
<i>Machine dimensions</i>	<i>1430x860x2100 mm</i>
<i>Weight</i>	<i>From 590 to 630 kg</i>
<i>Hood dust extractor</i>	<i>Diameter 160 mm</i>
<i>Capacity</i>	<i>2000 m³/h</i>